## Snorkel S4732E

## **Electric Slab Scissor Lifts**

| DIMENSIONS               | S4732E |
|--------------------------|--------|
| Max. working height      | 38 ft  |
| Max. platform height (A) | 32 ft  |
| TO 1 ( 1)                | 06.    |

Platform size (stowed) 86 in x 41.5 in Platform size (extended) 134 in x 41.5 in

Deck extension length (B) 48 in
Overall length (D) 89 in
Overall width (C) 47 in
Stowed height (E) 95 in
Min. height (guardrails folded) 76.5 in
Ground clearance (stowed) 3 in
Ground clearance (elevated) .75 in

## **PERFORMANCE**

| Platform capacity           | 700 lbs |
|-----------------------------|---------|
| Max. wind speed             | 28 mph  |
| Max. drive height           | 32 ft   |
| Max. drive speed (elevated) | 0.4 mph |
| Max. drive speed (stowed)   | 2.0 mph |
| Gradeability                | 25%     |
| Inside turning radius       | 10 in   |
| Outside turning radius      | 91 in   |
|                             |         |

Tires 15 in x 5 in, non-marking

rubber

Controls proportional
Drive system 2 wheel drive

**POWER** 

Power source 4 x 6V 240amp hour batteries

Charger 90-240V 25amp

**WEIGHT** 

Weight 5500 lbs